



中国国家强制性产品认证证书

证书编号: 2006010305207836

委托人名称、地址

Rockwell Automation, Inc.
1201 South Second Street, Milwaukee WI 53204, USA

生产者(制造商)名称、地址

Rockwell Automation, Inc.
1201 South Second Street, Milwaukee WI 53204, USA

生产企业名称、地址

罗克韦尔自动化制造(上海)有限公司
上海浦东新区华东路5001号 金桥出口加工区(南区)3号地块

产品名称和系列、规格、型号

按钮开关及指示灯

800FD... D7D... Ui:300V;Ith:5A;AC-15:Ue/Ie:120V/3A, 240V/1.5A; DC-13:Ue/Ie:125V/0.22A, 250V/0.1A; 指示灯:Ue:AC/DC6V, 12V, 24V, 48V, 120V, 240V; 安装孔径:22.5mm;防护等级IP20, IP66(工作面);型号详见附录

产品标准和技术要求

GB 14048.5-2008

上述产品符合强制性产品认证实施规则
CNCA-01C-011:2007的要求,特发此证。

发证日期: 2011年11月04日 有效期至: 2015年12月31日

证书有效期内本证书的有效性依据发证机构的定期监督获得保持。

本证书为变更证书,证书首次颁发日期: 2006年10月31日

本证书的相关信息可通过国家认监委网站www.cnca.gov.cn查询



主任:

中国质量认证中心

中国·北京·南四环西路188号9区 100070

<http://www.cqc.com.cn>



Q 0480212



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

No. : 2006010305207836

NAME AND ADDRESS OF THE APPLICANT

Rockwell Automation, Inc.
1201 South Second Street, Milwaukee WI 53204, USA

NAME AND ADDRESS OF THE MANUFACTURER

Rockwell Automation, Inc.
1201 South Second Street, Milwaukee WI 53204, USA

NAME AND ADDRESS OF THE FACTORY

Rockwell Automation Manufacturing (Shanghai) Ltd.
3# block, Shanghai Jinqiao Export Processing Zone, 5001 Hua Dong Road,
Pudong, Shanghai, P.R.China

NAME, MODEL AND SPECIFICATION

Push Button and Indicator Light

800FD... , D7D... Ui:300V;Ith:5A;AC-15:Ue/Ie:120V/3A, 240V/1.5A; DC-
13:Ue/Ie:125V/0.22A, 250V/0.1A; Indicator
Light:Ue:AC/DC6V, 12V, 24V, 48V, 120V, 240V; Aperture:22.5mm;IP20, IP66(Working
face);See the Appendix

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 14048.5-2008

This is to certify that the above mentioned products have met the
requirements of implementation rules for compulsory certification(REF
NO. CNCA-01C-011:2007).

Date of issue: Nov. 04, 2011 Date of expiry: Dec. 31, 2015

Validity of this certificate is subject to positive result of the regular
follow up inspection by issuing certification body until the expiry date.

Date of original certification: Oct. 31, 2006

This certificate can be verified through CNCA's website: www.cnca.gov.cn



President:

Wang Kejiao

CHINA QUALITY CERTIFICATION CENTRE

Section 9, No.188, Nansihuan Xilu, Beijing 100070 P.R.China

<http://www.cqc.com.cn>



Q 0480212



中国国家强制性产品认证证书

附录:

第 1 页 共 4 页

证书编号: 2006010305207836

纸号: 480212

型号的解释:

800FD	-	F	1	X	0	1	-	BP
I		II	III	IV	V	VI		VII

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type E – Push button, non-illuminated, momentary, extended F – Push button, non-illuminated, momentary, flush
III.	Assortment of colors Any number 0 through 9 – Operator cap color and legend
IV.	Type of Wire Termination X – For Stripped Wire R – For Ring Lug
V.	Number of N.O. Contacts 0, 1 or 2
VI.	Number of N.C. Contacts 0, 1 or 2
VII.	Packing Options (With -BP means products are shipped in bulk packing) Letters may be used to denote packaging options

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国·北京·南四环西路188号9区 100070

<http://www.cqc.com.cn>





中国国家强制性产品认证证书

附录:

第 2 页 共 4 页

证书编号: 2006010305207836

纸号: 480212

800FD Emergency Stop Operator Modules:

800FD	-	MT	4	4	X	2	0	-	BP	
I		II	III	IV	V	VI	VII		VIII	

I.	Product Line 800FD - 22.5 mm monolithic devices, Allen-Bradley D7D - 22.5 mm monolithic devices, Sprecher + Schuh
II.	Operator Type MT - Mushroom button, non-illuminated, push-pull/twist-to-release
III.	Mushroom Button Size 3 - 30 mm 4 - 40 mm 6 - 60 mm
IV.	Assortment of colors Any number 0 through 9 is used to denote operator color and legend
V.	Type of Wire Termination X - For Stripped Wire R - For Ring Lug
VI.	Number of N.O. Contacts 0, 1 or 2
VII.	Number of N.C. Contacts 0, 1 or 2
VIII.	Packing Options Letters may be used to denote packaging options

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国·北京·南四环西路188号9区 100070

<http://www.cqc.com.cn>





中国国家强制性产品认证证书

附录:

第 3 页 共 4 页

证书编号: 2006010305207836

纸号: 480212

800FD	-	S	B	3	2	X	I	1	-	BP
I		II	III	IV	V	VI	VII	VIII		IX

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type S – Selector switch, non-illuminated, standard knob
III.	Operator Function B – Spring return from left and right L – Spring return from left M – Maintained R – Spring return from right
IV.	Switch Positions 2 – Two positions 3 – Three positions
V.	Assortment of colors Any number 0 through 9 is used to denote operator color and legend
VI.	Type of Wire Termination X – For Stripped Wire R – For Ring Lug
VII.	Number of N.O. Contacts 0, 1 or 2
VIII.	Number of N.C. Contacts 0, 1 or 2
IX.	Packing Options Letters may be used to denote packaging options

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>





中国国家强制性产品认证证书

附录:

第 4 页 共 4 页

证书编号: 2006010305207836

纸号: 480212

800FD Pilot Light Operator Modules:

800FD	-	P	3	D	0	R	-	BP	
I		II	III	IV	V	VI		VII	

I.	Product Line 800FD – 22.5 mm monolithic devices, Allen-Bradley D7D – 22.5 mm monolithic devices, Sprecher+Schuh
II.	Operator Type P – Pilot light
III.	Color Any number 0 through 9 is used to denote operator color
IV.	Lamp Style D – Incandescent N – LED
V.	Voltage / Lamp Any number 0 through 9 is used to denote lamp and voltage
VI.	Type of Wire Termination Blank – For Stripped Wire R – For Ring Lug
VII.	Packing Options Letters may be used to denote packaging options

注: 此附录与证书同时使用时有效。



主任:

中国质量认证中心

中国 · 北京 · 南四环西路 188 号 9 区 100070

<http://www.cqc.com.cn>

